

Linen Tower Assembly Instructions

To reduce the chance of damage and to ease handling the linen tower is shipped in three pieces: Lower section, upper section and the crown molding.

To assemble these you will need

1. Medium Philips (star) screw driver
2. Carpenters glue
3. Paper towel or clean rag

We supply

1. Screws
2. Dowels

Step by Step Instructions

Assemble the linen tower in the room where it will be installed.

1. Place the upper section upside down with the top on the floor (Pic 1).
2. Place a few drops of glue in the 4 dowel holes (Pic 2) and push the 4 dowels into the holes until they can go no further (Pic 3).
3. Place a few drops of glue in the 4 dowel holes of the lower unit and place the upper unit on top of lower unit, aligning the dowels and holes (Pic 4).
4. Wipe off any excess glue.
5. Crown molding is installed using the provided screws. The crown molding has predrilled holes. Align the crown molding to the top of the cabinet and secure using screws (Pic 5). If the linen tower is being installed next to a wall, you will want to cut the crown molding to its desired size prior to permanently installing it.
6. If you're installing the linen tower against a wall and you ordered a filler, it may be shipped in one or two pieces. If your filler is in two pieces, the shorter 33" piece should be installed on the bottom section of the linen tower making the seam less noticeable (Pic 6).

Pic 1




Pic 2



Pic 3



Pic 4



Pic 5



Pic 6

