

Project Planner

PROJECT PLANNER



PLANNING TIPS

1. Accurately measure your bathroom. Make note of plumbing locations, electrical outlets, light fixtures and available wall depth at a doorway (our tops are 22½" deep). If your vanity is going next to the toilet, you should allow a minimum of 15" from the centre of the toilet to the edge of the vanity.
2. Using the design grid and referring to the Layout Options on page 8 and Cabinet line drawings on page 13, design your bathroom. Your dealer is there to assist you with any questions you may have.
Note: The stone tops are 1½" larger than the cabinet, so for example a 48" cabinet has a 49½" top, allowing for ¾" per side overhang or filler if the cabinet is up against a wall.
3. Select your cabinet colour, stone top colour, mirror size, sink colour and choose the desired drilling pattern for your faucets.
4. If your cabinet is up against a wall, don't forget to order a filler for a perfect fit.
5. If your cabinet sits between two walls we can cut down your stone top and add a side splash. Our largest top is 61½". Example: A 51" wall opening would require a 48" cabinet with a 4" filler to be cut down on-site, and a 61½" top cut down to 50" with an added side splash.
Note: We suggest accurately measuring the opening and ordering the top ¼" smaller to allow some room to fit the top in place. NEVER force the stone top in place. If your walls are out of square, notch the drywall to allow the top to sit flush on the cabinet with no stress or pressure on the granite. Once set in place your stone top is very durable and will last a lifetime, but while handling and installing it is fragile, please treat your stone top as though it were glass. Visit our website for installation instructions.
6. Review and place order with your dealer. Expect delivery within 2 to 3 weeks. Your dealer has our delivery schedule.